

M12-YAGI Directional Cellular / WiFi HaLow Antenna Directional Cellular 4G LTE CBRS 5G NR / WiFi HaLow Includes1ft Coax Cable / Tilt-Bracket Mount * Contact Us For M12-YAGI WiFi HaLow Configuration Options

M12-Yagi Log Periodic Directional Antenna w/Tilt L-Bracket Mount Multi Carrier YAGI Directional Cellular 4G LTE CBRS 5G / WiFi HaLow Includes 1ft Coax Cables / Tilt-Bracket Mount Hardware	
4G LTE CBRS 5G NR Frequency Range WiFi HaLow Frequency Range	617-960MHz / 1690-2700MHz / 3300-4000Hz 902~928Mhz
4G 5G CBRS Avg Peak Gain: <i>Isotropic</i> WiFi HaLow Avg Peak Gain: <i>Isotropic</i>	10dBi / 12dBi / 12dBi 10dBi
Horizontal Half-Power Beamwidth (°)	75° / 60° / 60°
Vertical Half-Power Beamwidth (°)	50° / 50° / 40°
Isolation (dB)	≥20dB
VSWR	≤2.0 / ≤2.0 / ≤1.5
Polarization Radiation Pattern	Vertical Directional
Front to Back Ratio (dB)	≥15 / ≥18 / ≥20
Nominal Impedance	50Ω
Max. Power	50W
Mechanical / Environmental Specifications	
Application	Outside
Radome	UV Resistant ABS
Dimensions	Length 445mm (17.5") / Height 205mm (8") / Thickness 38mm (1.5")
Coax Cables	1ft AGA200 Coax Cables – N Female Extension Cables Sold Separately All Standard Connector Ends Available (Including FAKRA)
Connector Types	N Female
Mounting Hardware (Stainless Steel)	Includes Tilt-Bracket Mount Hardware w/ 2 x U-Bolt Sets
Mounting Mast Diameter	1.5"~2.0" / 38mm~51mm
Ingress Protection	IP67
Humidity	5%~95%
Wind Velocity	130 MPH
Operating Temp (°F)	-40° / +158° (°F)
Weight	2.2lbs / 1kg Includes mounting hardware

M12-YAGI Series Directional Cellular Antenna w/ 1ft Coax Cables. Includes Tilt L-Bracket Mount Hardware "Built To Spec" Custom Extension Cable Options are Available. Contact us for details.





M12-YAGI Directional Cellular / WiFi HaLow Antenna Directional Cellular 4G LTE CBRS 5G NR / WiFi HaLow Includes1ft Coax Cable / Tilt-Bracket Mount * Contact Us For M12-YAGI WiFi HaLow Configuration Options

Supported Cellular Service Provider Networks	
Verizon	Verizon 4G LTE 5G NR Bands 4G LTE: <i>B2 B4 B5 B13 B46 B48 B66 (CBRS B48)</i> 5G NR: <i>N2 N5 N66 N77</i> Carriers (MVNOs) using Verizon Network: <i>Reach Mobile, Red Pocket Mobile, Spectrum Mobile, Ting</i> <i>Total, Tracfone, Twigby, US Mobile, Visible, Xfinity Mobile</i>
T-Mobile	Mobile 4G LTE 5G NR Bands 4G LTE: <i>B2 B4 B5 B12 B25 B26 B41 B48 B66 B71 (CBRS B48)</i> 5G NR: <i>N25 N41 N66 N71</i> Carriers (MVNOs) using T-Mobile Network <i>Mint Mobile, TextNow, Lyca Mobile, Metro, Red Pocket Mobile</i> <i>Republic Wireless, Simple Mobile, Ting, Tracfone, US Mobile</i>
AT&T	AT&T 4G LTE 5G NR Bands 4G LTE: B2 B4 B5 B12 B14 B17 B29 B30 B48 B66 (CBRS B48) GSM: 1900MHz 5G NR: N2 N5 N66 N77 Carriers (MVNOs) using AT&T Network Cricket Wireless, Net 10 Wireless, Red Pocket Mobile, Straight Talk
Supported Cellular Bands	
5G NR Bands	n1 n2 n3 n5 n7 n8 n12 n13 n14 n18 n20 n25 n26 n28 n29 n30 n38 n40 n41 n48-CBRS n66 n71 n75 n76 n77 n78 n79 C-band
4G LTE Bands	B1 B2 B3 B4 B5 B7 B8 B12 B13 B14-FirstNet B17 B18 B19 B20 B25 B26 B28 B29 B30 B32 B38 B39 B40 B41 B42 B43 B46-LAA B48-CBRS B66 B71
3G Bands	B1 B2 B3 B4 B5 B6 B8 B9 B19
Supported WiFi IEEE Standards	
* WiFi HaLow	WiFi HaLow (802.11ah) * Contact Us For M12-YAGI WiFi HaLow Configuration Options





M12-YAGI Directional Cellular / WiFi HaLow Antenna Directional Cellular 4G LTE CBRS 5G NR / WiFi HaLow Includes1ft Coax Cable / Tilt-Bracket Mount * Contact Us For M12-YAGI WiFi HaLow Configuration Options

M12-YAGI Directional Cellular 4G LTE CBRS 5G NR / WiFi HaLow Dimensions / Tilt L-Bracket Mount

17.5" / 444.5mm



Includes Tilt L-Bracket Mount





M12-YAGI Series Directional Cellular Antenna w/ 1ft Coax Cables. Includes Tilt L-Bracket Mount Hardware "Built To Spec" Custom Extension Cable Options are Available. Contact us for details.

