

| MDP44W / MDP42W Directional Multi MIMO 2 x / 4 x WiFi 6 Antenna Multi Band MIMO WiFi 6 (2.4~6GHz) / Bluetooth (2.4GHz) Includes 15ft Coax Cables / Articulating Tilt-Bracket Mount Hardware | | |
|---|--|--|
| WiFi 6 / Bluetooth (2.4GHz) Frequency Range | 2.4-2.5GHz / 4.9-6GHz (Concurrent) | |
| WiFi 6 / Bluetooth Avg. Peak Gain: Isotropic | 6dBi / 6dBi | |
| Horizontal Half-Power Beamwidth | 105° / 110° | |
| Vertical Half-Power Beamwidth | 65° / 55° | |
| Isolation (dB) | ≥20dB | |
| Front to Back Ratio (dB) | ≥20dB | |
| VSWR | ≤2.0 / ≤2.0 | |
| Nominal Impedance | 50Ω | |
| Polarization Radiation Pattern | MIMO 4 x Vertical / MIMO 6 x Vertical Directional | |
| Max. Power | 50W | |
| | Supported WiFi IEEE Standards | |
| WiFi 1-6 | WiFi 1 WiF 2 (802.11ba) WiFi 3 (802.11g) WiFi 4 (802.11n) WiFi 5 (802.11ac) WiiFi 6 6E (802.11ax) WiFi 7 (802.11be) | |
| Ν | lechanical / Environmental Specifications | |
| Application | Outside / Inside | |
| Radome | UV Resistant ABS Height: 5.6" / 142mm Width: 9.6" / 245mm Depth: 1.4" / 36mm | |
| Coax Cables | 15ft AGA200 Coax Cables (2-Lead / 4-Lead) Extension Cables Sold Separately | |
| Connector Types | RP SMA Male All Standard Connector Ends Available (Including FAKRA) | |
| Mounting Hardware (Stainless Steel) | Articulating Tilt-Bracket Mount Hardware w/ 2 x U-Bolt Sets | |
| Mounting Mast Diameter | 2"~2.25" / 51mm~57mm | |
| Ingress Protection | IP67 | |
| Humidity | 5%~95% | |
| Wind Velocity | 125 MPH | |
| Operating Temp (°F) | -40° / +158° (°F) | |
| Weight | 3lbs / 1.4kg Includes Mounting Hardware | |





MDP44W / MDP42W MIMO Directional WiFi 6 Antenna Dimensions / Articulating Tilt-Bracket Mount / 15ft Coax Cables

> Height: 5.6" / 142mm Width: 9.6" / 245mm Depth: 1.4" / 36mm



9.6" 245mm







| MDP42W Directional MIMO WiFi Series Antenna Configuration Options Includes Articulating Tilt-Bracket Mount w/ 2 x 15ft Coax Cables | |
|---|--|
| Configuration | MDP42W -15-RP: Directional MIMO WiFi Bracket Mount Antenna w/ 2 x 15ft Coax Cables – RP SMA Male |
| Options | MDP42W -15-FAKRA: Directional MIMO WiFi Bracket Mount Antenna w/ 2 x 15ft Coax Cables – FAKRA |

MDP42W MIMO 2 x Directional WiFi







| MDP44W Directional MIMO WiFi Series Antenna Configuration Options Includes Articulating Tilt-Bracket Mount w/ 4 x 15ft Coax Cables | |
|---|--|
| Configuration | MDP44W -15-RP: Directional MIMO WiFi Bracket Mount Antenna w/ 4 x 15ft Coax Cables – RP SMA Male |
| Options | MDP44W -15-FAKRA: Directional MIMO WiFi Bracket Mount Antenna w/ 4 x 15ft Coax Cables – FAKRA |

MDP44W MIMO 4 x Directional WiFi



