

XHD NMO Omni Series M2M IoT Antenna Specifications  
 Cellular 4G LTE CBRS 5G NR / WiFi HaLow (902~928Mhz)  
 Optional NMO Mount w/ 15ft Coax Cable

4G LTE CBRS 5G NR Frequency Range	617-960MHz / 1710-4000MHz
4G CBRS 5G NR Avg Peak Gain <i>Isotropic</i> WiFi HaLow Avg Peak Gain <i>Isotropic</i>	(3dBi) 617~960MHz / (5dBi) 1710-4000MHz / (5dBi) CBRS 3.5GHz) (5dBi) WiFi HaLow (902~928Mhz)
Typical Efficiency 4G 5G	617-960MHz >50% 1710-4000MHz >50%
Typical Efficiency WiFi <i>HaLow</i>	>50%
Horizontal Half Power Beamwidth	360° / 360°
Vertical Half Power Beamwidth	40° / 20°
VSWR	≤1.5 / ≤1.5
Nominal Impedance	50Ω
Polarization Radiation	Vertical Omni Directional
Max. Power	50W

Mechanical / Environmental Specifications

Application	Outside / Inside
Mast	Stainless Steel Height: 12.75" / 324mm
Mount Type	NMO Mount
Mount Option	Optional NMO Mount w/15ft Coax Cable (Sold Separately)
Antenna Connector Type	All Standard RF Connector Ends Available
Ingress Protection	IP67
Wind Velocity	150 MPH
Operating Temp (°F)	-40° / +158° (°F)
Weight	1lbs / 0.45kg Including Optional Mounting Hardware



XHD NMO Omni Series Cellular 4G 5G NR Antenna  
 Omni Directional Cellular 4G LTE CBRS 5G NR / WiFi HaLow  
 NMO Mount Base w/ 15ft Coax Cable (Sold Separately)  
 \* Contact Us For XHD NMO HaLow WiFi Configuration Options

**Supported Cellular Service Provider Networks**

Verizon	<p>Verizon 4G LTE 5G NR Bands          4G LTE: B2 B4 B5 B13 B46 B48 B66 (CBRS B48)          5G NR: N2 N5 N66 N77</p> <p>Carriers (MVNOs) using Verizon Network:  <i>Reach Mobile, Red Pocket Mobile, Spectrum Mobile, Ting Total, Tracfone, Twigby, US Mobile, Visible, Xfinity Mobile</i></p>
T-Mobile	<p>Mobile 4G LTE 5G NR Bands          4G LTE: B2 B4 B5 B12 B25 B26 B41 B48 B66 B71 (CBRS B48)          5G NR: N25 N41 N66 N71</p> <p>Carriers (MVNOs) using T-Mobile Network  <i>Mint Mobile, TextNow, Lyca Mobile, Metro, Red Pocket Mobile Republic Wireless, Simple Mobile, Ting, Tracfone, US Mobile</i></p>
AT&T	<p>AT&amp;T 4G LTE 5G NR Bands          4G LTE: B2 B4 B5 B12 B14 B17 B29 B30 B48 B66 (CBRS B48)          GSM: 1900MHz          5G NR: N2 N5 N66 N77</p> <p>Carriers (MVNOs) using AT&amp;T Network  <i>Cricket Wireless, Net 10 Wireless, Red Pocket Mobile, Straight Talk</i></p>

**Supported Cellular Bands**

5G NR Bands	n1 n2 n3 n5 n7 n8 n12 n13 n14 n18 n20 n25 n26 n28 n29 n30 n38 n40 n41 n48-CBRS n66 n71 n75 n76 n77 n78 n79 C-band
4G LTE Bands	B1 B2 B3 B4 B5 B7 B8 B12 B13 B14-FirstNet B17 B18 B19 B20 B25 B26 B28 B29 B30 B32 B38 B39 B40 B41 B42 B43 B46-LAA B48-CBRS B66 B71
3G Bands	B1 B2 B3 B4 B5 B6 B8 B9 B19

**Supported WiFi IEEE Standards**

* WiFi HaLow	WiFi HaLow (802.11ah) * Contact Us For XHD HaLow WiFi Configuration Options
--------------	---



XHD NMO Omni Series Cellular 4G 5G NR Antenna  
 Omni Directional Cellular 4G LTE CBRS 5G NR / WiFi HaLow  
 NMO Mount Base w/ 15ft Coax Cable (Sold Separately)  
 \* Contact Us For XHD NMO HaLow WiFi Configuration Options

XHD NMO Omni Series Antenna  
 Dimensions / Optional NMO Mount

XHD-NMO Antenna Mast



323.85mm  
 12.75"

NMO Base



Optional  
 NMO Mount w/15ft RG58 Coax Cable  
 All Standard Connector Ends Available  
 Sold Separately



NMO Base

XHD NMO Omni Series Cellular Antenna – Optional NMO Mount w/15ft. Coax Cable Sold Separately  
 "Built To Spec" Custom Cable Options are Available. Contact us for details.

