



M1200 Omni Directional 4G LTE CBRS 5G NR Antenna
 Cellular 4G LTE CBRS 5G NR / WiFi 2.4GHz 5GHz~6GHz
 Bracket Mount Option / Mag Mount Option / Outside Use
[*Optional J-Pipe Mount](#)

M1200 Omni Directional Cellular 4G LTE CBRS 5G NR Antenna Multi-Carrier Cellular 3G 4G LTE CBRS 5G NR / WiFi 2.4GHz	
Multi-Carrier / Multi-Technology 4G LTE CBRS 5G NR Compliant	Verizon 4G 5G (DSS) Bands: B2 B4 B5 B13 B46 B48 B66 T-Mobile 4G 5G Bands: B2 B4 B5 B12 B25 B26 B41 B66 B71 n25 n41 n66 n71 AT&T 4G 5G Bands: B2 B4 B5 B12 B14 B17 B29 B30 B66 n5 5G NR Bands: n77 n78 n79 CBRS Band: B48
4G 5G Frequency Range WiFi Frequency Range	617-960MHz / 1710-6000MHz 2.4-2.5GHz
4G 5G NR Avg. Peak Gain: Isotropic WiFi Avg. Peak Gain: Isotropic	(6dBi) 617-960MHz / (8dBi) 1710-6000MHz / (6dBi) CBRS 3.5GHz (10dBi) 2.4-2.5GHz
Horizontal Half Power Beamwidth	360° / 360°
Vertical Half Power Beamwidth	40° / 20°
VSWR	≤2.0 / ≤2.0
Impedance	50 Ohms
Polarization	Vertical
Max. Power	50W
Dimensions	Height: 24" / 612mm - Mast Dia: 0.8" / 20mm - Base Dia: 1" / 24mm
Mast	Fiberglass Encased Brass Stack
Operating Temperature	-40° to 158° (°F)
Wind Velocity	120 MPH
Ingress Protection	IP67
Mount Options	L-Bracket w/U-Bolt Mounting Hardware 5" Magnetic Mount Base w/15ft Coax Cable
U-Bolt Mounting Diameter (L-Bracket Mount)	1.5"~2" / 40mm~50mm
Antenna Connector Type	N Female Base
Net Weight	1lbs / .45kg - Including L-Bracket Mounting Hardware 2.2lbs / 1kg - Including 5" Magnetic Mount w/15ft Coax Cable

M1200 Series Omni Enterprise Grade Antenna. Includes L-Bracket Mount Hardware / N Female
 "Built To Spec" Custom Extension Cable Options are Available. Contact us for details.





M1200 Omni Directional 4G LTE CBRS 5G NR Antenna
 Cellular 3G 4G LTE CBRS 5G NR / WiFi 2.4GHz
 Bracket Mount Option / Mag Mount Option / Outside Use
[*Optional J-Pipe Mount](#)



612mm
24"

N Female

L-Bracket Option
Includes U-Bolt Sets



Mag Mount Option
N Male Base Connector
Includes 15ft Coax Cable

